

DuPont™ AirGuard® Tape

Product Description & Application

A high performance, flexible and universal Air & Vapour Control Layer Tape (AVCL-Tape). Suitable for airtight sealing of membrane laps, joints, junctions, windows and doors and sealing around penetrations such as pipework, wiring and structural elements. Good adhesion to various smooth and slightly rough substrates; timber, masonry, aluminium, steelwork, UPVC, PE and PP membranes. Recommended for internal use with AirGuard® AVCL's.

Product composition

| | |
|----------------|-------------------------|
| Carrier: | Flexible PE film, white |
| Adhesive: | Acrylic |
| Release liner: | Siliconized paper |

Specifications

| PROPERTY | STANDARD | VALUE |
|--------------------------|-------------------------|------------------------------|
| Stylename | | 1310V |
| Colour | | White |
| Thickness | DIN EN 1942 | approx. 270 µm |
| Basis weight | | approx. 375 g/m ² |
| Temperature range | | -40 °C to 70 °C |
| Installation temperature | | > -5°C (*) |
| Airtightness (**) | DIN 4108-2 DIN 18542 | airtight meets BG R |
| Tensile strength | DIN EN 14410 | approx. 25 N/cm |
| Elongation at break | DIN EN 14410 | approx. 450 % |
| Adhesion to steel | DIN EN 1939 | approx. 12 N/cm |
| GEV-EMICODE | EC1 Plus | |

(*): depending on the substrate this may be slightly different. A self sticky testing may be necessary before starting the installation.

(**): Measured at a pressure difference of 600Pa. Tested on an aluminum surface.

Use and Care recommendations

- Highly flexible, hand-tearable reinforced carrier
- Good temperature resistance
- High water vapour resistance
- Acrylic adhesive with excellent ageing resistance
- Solvent free adhesive
- Up to 4 months resistant to UV (when used for outdoor applications)
- Not sensitive to contact with water
- In cases where adhesion is not effective due to the surface of the building material being very porous, non-stable, chalky or sandy the DuPont™ Tyvek® Primer is recommended beforehand
- The surface should be free from dirt, moisture, ice, grease and other materials which potentially reduce adhesion strength

Storage recommendations:

- Store rolls in original packaging lying flat in a dry and clean place at temperatures between +5°C & 35°C and away from direct sunlight

DuPont de Nemours
(Luxembourg) S.à r.l.
Rue General Patton,
L - 2984 Luxembourg
Tel.: +352 3666 5885
tyvek.info@lux.dupont.com

www.building.dupont.co.uk

This information corresponds to our current knowledge on the subject. It is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for any application other than the application as specified herein. This information may be subject to revision as new knowledge and experience becomes available. Since we cannot anticipate all variations in actual end-use conditions, DuPont makes no warranties and assumes no liabilities in connection with any use of this information for applications other than the application as specified herein. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right. Product safety information is available on request. This data sheet is a printed document and is valid without signature.

Date: April 14, 2020

DUPONT
Tyvek