



---

## DuPont™ Tyvek® Supro – Below pitch roof installation

---

NBS: P10 320      Also: H20, H21, H30, H31, H60, H61, H62, H64, H65, H67, H92,  
K20, K21, M30

For additional information on our product(s) and guidance on how to use them you may wish to refer to our step by step Installation Guide and videos. This and other useful information is on our web site:

[www.building.dupont.co.uk](http://www.building.dupont.co.uk)

For help with a project please contact the DuPont Building Knowledge Centre. (Contact details can be found at the end of this Installation Sheet).

**Type LR Underlay** to EN 13859-1: shall be **Tyvek® Supro** as supplied by DuPont Performance Building Solutions, HERE, 470 Bath Rd, Arno's Vale, Bristol. BS4 3AP. UK

### Storage

Rolls of Tyvek® Supro should be stored palletised or on their sides on a smooth clean surface, under cover and protected from direct sunlight.

### General

Care should be taken when handling the membrane to prevent tears and punctures occurring. Any that do occur should be repaired with Tyvek® Acrylic Tape (2060B).

### Double felt method - Tyvek® Supro is installed in two layers with staggered laps between each layer.

#### Eaves:

Lay an appropriate UV resistant eaves sheet over the fascia board/rafter ends, extend into the gutter and fix into place with felt nails. Lay Tyvek® Supro parallel to the eaves overlapping the eaves sheet and taking the membrane to the outside edge of the fascia board or rafter ends. Bond the membrane to the eaves sheet with Tyvek® Double-sided Tape to form a weather-tight seal.

Overlay the first layer of Tyvek® Supro with a second 'half-width' and line up with the lower layer's bottom edge. When consecutive runs of membrane are installed a staggered lap pattern will be created. Continue laying Tyvek® Supro in two layers, so the entire roof area is 'double-felted.'

#### Fixing

Tyvek® Supro should be fixed with large headed felt nails which will self-seal the penetration. Fixings should be positioned at 300mm max centres to each rafter (or counter batten). Rafter spacing should be no more than 600mm centre to centre.

#### Laps

Maintain 150mm horizontal laps between each sheet. Any vertical laps should be minimum 300mm and positioned over rafters.

#### Unsupported underlay

Tyvek® Supro should be laid horizontally across the roof slope, with a nominal drape of 10mm and fixed with stainless-steel staples or preferably large headed felt nails which will self-seal the penetration. Fixings should be positioned at maximum 300mm centres to rafters (or counter battens). Laps should be sealed with Tyvek® Acrylic Tape (2060B) to comply with standards on wind uplift. Alternatively, where circumstances allow, a tiling batten may be positioned over the lap. Users should check the specific zonal wind uplift restrictions applicable to the site location, as well as the height and exposure parameters in accordance with the current version of BS5534 Annex A.

#### Supported underlay

Tyvek® Supro should be pulled over the support and secured with appropriately sized counter battens. Stainless-steel staples or large headed felt nails may be used to temporarily secure the membrane, which must be later covered by the counter battens. Depending on the site location and the associated exposure to driving rain it may be advisable to install a strip of Tyvek® Butyl Tape beneath the counter batten to help seal the fixing penetrations.

#### Ply/OSB sheathing - Ventilated

**These vapour resistant board materials do not allow adequate vapour diffusion and therefore should not be installed in non-ventilated applications above insulation.** Ventilation at eaves and ridge and a continuous 50mm cross ventilation path must be maintained beneath the sheathing in accordance with the current version of BS5250. Tyvek® Supro may be installed over plywood or OSB sheathing, where the insulation is to be installed above, ie. warm roofs.

#### Scottish Sarking: Non-ventilated

To maintain vapour permeability, timber boarding should be 150mm wide with 2mm gaps as per BBA certificate 08/4548 or NSAI certificate 04/0157. Two layers of Tyvek® Supro should be laid directly over the timber sarking, with staggered laps (as above) and secured with large headed felt nails (staples should not be used). The membrane should be laid horizontally with laps sealed as per the unsupported criteria above to comply with standards on wind uplift. Slates are fixed directly through into the boarding.

#### Ridge: Non-ventilated

A minimum of two layers of Tyvek® Supro should extend over the ridge and lap at least 150mm down each side so that a 300mm wide double layer is formed over the centre-line.

#### Ridge: Ventilated (for NHBC requirements)

Install Tyvek® Supro continuously over the ridge to provide protection during construction. Immediately prior to fitting the ridge tiles, cut the membrane away along the ridge line to maintain the ventilation path.

#### Hip

The top two layers of Tyvek® Supro underlay should be taken up to the hip from one side and folded back to form a drainage welt. The underlay from the opposing roof slope should extend across the hip and over the first underlay to form a triple layer of membrane over the hip rafter. Once the membrane is fixed into place it may be trimmed back, but a minimum lap of 300mm should be maintained.

### Valley (for tiles, lead, GRP, etc.):

This process should result in three layers of membrane being installed, providing protection to the valley.

1. Lay a strip of Tyvek® Supro (minimum 600mm wide) vertically down the centre line of the valley.
2. Dress Tyvek® Supro from one roof pitch and extend across the valley to the opposing roof slope, covering entirely the first Tyvek® strip.
3. Repeat with the underlay from the remaining roof pitch, extending to the opposing roof slope.

With the double-felt method, the top two layers of Tyvek® Supro should be used in the process above. For each stage, fix the Tyvek® Supro underlay into place with large headed felt nails. During the process, care should be taken to ensure the membrane is formed to the valley shape as much as possible. This is to avoid penetrating the membrane with the valley lining or battens when later installed directly over.

### Chimneys & roof windows:

Tyvek® Supro should be formed around chimneys & roof windows, turning the underlay up against the detail and terminating behind flashings (if present) to eliminate water ingress. Where appropriate, seal the underlay against the detail with Tyvek® Acrylic Tape (2060B).

### Penetrations:

Window corners, soil vent pipes and cable penetrations can be effectively sealed with Tyvek® Acrylic Tape (2060B) or Tyvek® FlexWrap EZ.

### Airtightness – sealing (optional)

Tyvek® Supro has been tested for 'Resistance to penetration of air' in accordance with EN 12114 achieving <0.25 m<sup>3</sup>/h.m<sup>2</sup> at 50 Pa. With all laps and penetrations sealed with Tyvek® Acrylic Tape (2060B), Tyvek® Supro will contribute to the overall airtightness of the building. If preferred, fixing penetrations can be sealed by applying Tyvek® Butyl Tape to the substrate before the membrane is installed.

**Compatibility:** Where timber treatments are used care should be taken to ensure they are touch-dry before the installation of the Tyvek® Supro underlay. Retrospective spray applied micro emulsions can also pose significant risk to polymer-based materials such as Tyvek®. Masking the membrane against preservative treatments should be considered.

### Temporary exposure period

Tyvek® Supro may be left exposed for a period not exceeding **4 months**, provided that the membrane is adequately secured in accordance with our recommendations. Site conditions and exposure to wind should be assessed to determine whether extra security measures for the membrane are required.

### Fire regulations

Tyvek® Supro has Fire Classification E in accordance with EN 13501-1. Care should be taken to determine suitability of this membrane for the intended application, with specific regard to building height and proximity to boundary. Users/specifiers should refer to their regional regulatory guidance documents in case there are any requirements or variations that may restrict the use of this product.

Video installation link: <https://www.dupont.co.uk/resource-center.html?BU=pbs&restyle=video>

---

## DuPont™ Tyvek® Supro – Below pitch roof installation notes

---

The 'double-felt' roof system using a Tyvek® underlay provides a solution for roof systems that are built below the minimum pitch for the tile or slate. This has become accepted practice for over 20 years by many local authorities throughout the UK where a building or design constraint existed.

Tyvek® Supro - installed in two layers with staggered laps has proven to be particularly useful for roofs that suffer from height restrictions such as with single storey lean-to extensions. It is quite common for these roofs to present a relatively small area and are therefore ideal for this method as they would be expected to discharge only a limited amount of rainfall. Whilst this method is very effective it's use is limited in main roofs, especially ones of two storey height. However, this method may be considered depending on the proposed pitch, location data and slate/tile selection.

Wherever possible, our standard pitched roof underlay Tyvek® Supro should be laid at a pitch suitable for the slate or tile that is being used. However, we will accept the 'double felt' method using the following rules as a general guide:

<u>Tile/slate min pitch</u>	<u>Double felt allowance</u>
12° - 19°	-3°
20° -29°	-4°
30° - 39°	-5°
40° +	please contact us

Following this system will ensure that the absolute minimum pitch allowed with two layers of Tyvek® Supro is 9° (for a tile which has a minimum pitch of 12°). A lower pitch may be acceptable for profiled metal clad industrial roofs or where a tile effect metal roof sheet is used eg. Metrotile, Britmet Tileform.

Rafter length should not exceed 9m for areas of normal exposure to driving rain and 6m for areas of high exposure.

Attention must be paid to details such as hips, valleys and large tilt fillets (eaves sprockets). These are considered 'weak points' in the system as they incorporate lower pitches than that of the main roof areas.

Consideration should also be given to details that penetrate the Tyvek® underlay such as soil vent pipes, chimneys & roof windows. The underlay should turn up against the detail and be sealed with Tyvek® Acrylic Tape (2060B) or correctly lapped to appropriate flashings. Any cuts and/or corners should be made good with Tyvek® Acrylic Tape (2060B) or Tyvek® FlexWrap EZ to prevent water ingress.

These factors all govern the risk of water penetration onto the roof underlay. **In all cases the underlay must be laid to a fall with no ponding of water on the underlay under any circumstances.**

This policy is not entirely rigid and approval may be given for pitches lower than those stipulated above, according to specific data associated with the proposed project. In these cases details such as roof area, height and location would need to be considered.

Our warranty for Tyvek® Supro is applicable to the double-felting method, provided it is installed in accordance with these guidelines.

For further advice on the use of Tyvek® membranes please contact BKC Technical: 0117 452 9050

Video installation link: <https://www.dupont.co.uk/resource-center.html?BU=pbs&restyle=video>

---

#### DuPont Performance Building Solutions

HERE  
470 Bath Rd  
Arno's Vale  
Bristol UK  
BS4 3AP

**0117 452 9050**

**Option 1:** Technical (Building Knowledge Centre)

**Option 2:** General Enquiries

Technical enquiries: [tyvek.construction@dupont.com](mailto:tyvek.construction@dupont.com)



**THE DUPONT™ TYVEK®  
BUILDING KNOWLEDGE CENTRE**

*- Science you can build on -*

[www.building.dupont.co.uk](http://www.building.dupont.co.uk)  
[www.energy-efficiency.dupont.com](http://www.energy-efficiency.dupont.com)

« DUPONT »  
**Tyvek.**

Recommendations as to methods, use of materials and construction details are based on the experience and current knowledge of DuPont and are given in good faith as a general guide to designers, contractors and manufacturers. This information is not intended to be a substitute for any testing you may need to conduct to determine, for yourself, the suitability of our products for your particular purposes. This information may be subject to revision as new knowledge, regulations and experience becomes available since we cannot anticipate all variations in actual end-use conditions. DuPont makes no warranties and assumes no liability in connection with any use of this information. Nothing in this publication is to be considered as a licence to operate under a recommendation to infringe any patent right.

Tyvek® construction membranes are manufactured by DuPont under an ISO 9001: 2015 Quality Assurance System.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2024 DuPont.