



When the Safety of Others and Long Term Building Performance is Essential

DuPont™ AirGuard® A2 FR AVCL Fire Retardant Membrane

– for internal lining of wall, ceiling and roof systems

DuPont™ Tyvek® FireCurb® Breather Membrane

– for external lining of wall systems



Tyvek® and AirGuard®
Airtightness
Tried and Tested



Class A2 Fire Retardant AVCL Membrane

DuPont™ AirGuard® A2 FR

Airtight Vapour Control Layer for use within the internal lining of roof, ceiling and wall systems



**FIRE
RETARDANT**

DuPont™ AirGuard® A2 FR AVCL: a Fire Retardant Airtight Vapour Control Layer for use within the internal lining of roof, ceiling and wall systems. Enhancing the building fabric in terms of airtightness, energy efficiency and moisture management, improving indoor air quality and providing exceptional fire safety to the building and its occupants.

Surpassing the Fire Regulations

Today the fire performance of materials used in buildings is under closer scrutiny than ever before and the regulations continue to be updated. DuPont has introduced a step change in their building membranes offering: a fire retardant AVCL with European Fire Classification A2.


Membrane & Tape System – Independent Classification: A2-s1,d0

For DuPont™ AirGuard® A2 FR AVCL to provide effective airtightness and vapour control it is crucial that all laps, junctions and penetrations are sealed. In order to give assurance that a complete system is ‘fire-safe,’ a full system test, including horizontal and vertical lap sealing with DuPont™ AirGuard® FR System tape has been successfully tested according to EN 13501-1 at the Prüfinstitut Hoch → Classification Report, KB-Hoch-200148-5, 18.08 2021.



DuPont™ AirGuard® A2 FR AVCL & tape system advantages at a glance

- Fire-retardant
- Reaction to fire: A2-s1, d0 to EN 13501-1: 2007+A1:2009
- AirGuard® A2 FR AVCL and DuPont™ AirGuard® FR System tape
- Suitable for all building types, heights and proximities
- High vapour resistance, limiting interstitial condensation
- Suitable for high humidity buildings, such as swimming pool halls etc
- Thermal benefit; low emissivity/reflective surface
- 100% Airtightness
- Extremely robust
- Exceptional tear and tensile strength characteristics
- 25 year warranty* for the AirGuard® A2 FR AVCL membrane
- Tested and classified for free-span, on mineral wool slab, gypsum plasterboard or fibre cement board
- Fire Classification surpasses all national building regulations and standards for construction materials used in walls in the UK and Ireland



DuPont™ AirGuard® FR
System Tape 1310FR



**THE DUPONT™ TYVEK®
BUILDING KNOWLEDGE CENTRE**
www.building.dupont.co.uk

Tyvek® FireCurb® breather membrane advantages at a glance

- Compliance with national Fire Regulations & Standards for use in hi-rise buildings
- Reaction to fire: B-s1,d0
- Self-extinguishes when ignited - limits propagation of flames
- Class W1 essential water resistance to EN 13859
- Halogen-free flame retardant coating considerably limits the formation of droplets and reduces smoke
- Greater safety during and after installation
- Long term investment protection
- Has all the tried, tested and trusted properties Tyvek® is known for
- Strong technical support for all Tyvek® and AirGuard® products

DuPont™ Tyvek® FireCurb® breather membrane

breather membrane for use in the external lining of wall systems



FLAME
RETARDANT

Tyvek® FireCurb® breather membrane: a flame retardant breather membrane for buildings based on a new patented technology, enabling a Euroclass B (EN 13501-1) that potentially saves lives and could prevent costly damages.

The building breather membrane that limits the propagation of flames

DuPont introduced a new level of building protection with the flame retardant breather membrane Tyvek® FireCurb®. When flames meet Tyvek® FireCurb®, they literally stop, die down ... and go out. The membrane includes all of the well-known properties of Tyvek®, adding flame retardancy for even more comprehensive protection of walls.

Tyvek® FireCurb® breather membrane advantages at a glance

- Compliance with national Fire Regulations & Standards for use in hi-rise buildings
 - Reaction to fire: B-s1,d0
 - Self-extinguishes when ignited - limits propagation of flames
 - Halogen-free flame retardant coating considerably limits the formation of droplets and reduces smoke
 - Greater safety during and after installation
 - Long term investment protection
- Includes all durable Tyvek® characteristics essential for energy efficient and condensation free buildings:
 - Class W1 water resistance to EN 13859
 - Vapour resistance meets BS 5250 guidance for breather membranes (<0.6 MN.s/g)
 - **IMPORTANT:** Not all fire retardant breather membranes, on the market, reach the required sd and water vapour resistance standard <0.6MN.s/g

DuPont™ AirGuard® A2 FR AVCL

Properties C €	Nominal
Style name and D code	5816X (D Code:- D15561632)
Roll size	1.2m x 50m
Thickness	0.15 mm
Mass per unit area	165 g/m²
Composition	Laminate of glass fibre-mesh with lacquered Aluminium foil
Reaction to fire* (EN13501-1)	A2-s1,d0 (membrane)
Reaction to fire* (EN13501-1)	A2-s1,d0 (membrane & AirGuard® FR System tape)
Water vapour transmission (Sd)	4.900 m
Water vapour resistance	24.000 MN.s/g
Emissivity	0.05
Thermal resistance (with airspace)	Walls: 0.66 m²K/W / Ceilings: 0.45 m²K/W
Water tightness (EN1928)	Pass (Type A)
Tensile force MD/XD	800/800 (N/500)
Nail tear resistance MD/XD	170/150 (N/50 mm)

Tested freehanging & affixed on underlaying materials with EN13501-1 fire class A1 or A2-s1, d0.

IMPORTANT: To compliment this product, a flame retardant breather membrane should be used on the external side of the wall system. For this purpose, we would recommend you use DuPont™ Tyvek® FireCurb®. Please see www.flameretardant.tyvek.com

DuPont™ Tyvek® FireCurb®

Properties C €	Nominal
Style name and D code	2066B (D Code:- D15085129)
Dimensions / Weight	1.5 x 50 m / 5.5 kg per roll
Composition	Flash-spun-bond HDPE with flame retardant coating
Reaction to fire*	(EN13501-1) B-s1,d0
Temperature resistance	-40 to +100° C
Water vapour transmission (Sd)	0.015 m
Water vapour resistance	0.075 MN.s/g (less than 0.6 MN.s/g to BS 5250:2011)
Mass per unit area	68 g/m²
Functional layer thickness	175 µm
CE-Certificate of Conformity	yes (0799-CPD-128)

*(if installed freehanging, on mineral wool & cementitious or gypsum boarding--> B-s1,d0 , if installed onto wood --> D-s2,d2)

IMPORTANT: To compliment this product in roof, ceiling and wall systems, a fire retardant air and vapour control layer (AVCL) should be used within the internal lining. For this purpose we would recommend you use DuPont™ AirGuard® A2 FR.

To achieve optimal airtightness, we recommend the use of the following adhesive accessories.

Tyvek® Acrylic Tape

Roll size:
75 mm x 25 m



AirGuard® FR System Tape

Roll size:
75 mm x 25 m



Tyvek® Butyl Tape

Roll size:
20 mm x 30 m or
50 mm x 30 m



Tyvek® Double-sided Tape

Roll size:
50 mm x 25 m



Tyvek® FlexWrap NF/EZ (Check for maximum tape width permitted)


Roll size Tyvek® FlexWrap NF:
15 cm x 23 m



Roll size Tyvek® FlexWrap EZ:
60 mm x 10 m




For more detailed information on all our tapes and accessories please refer to pages 68 - 79.



DuPont™ Tyvek® FireCurb® breather membrane

Breather membrane for use in the external lining of wall systems.
Tyvek® FireCurb® Installation Sheet



Class A2 Fire Retardant AVCL Membrane DuPont™ AirGuard® A2FR

Airtight Vapour Control Layer for use within the internal lining of roof, ceiling and wall systems
AirGuard® A2FR Installation Sheet.

ENHANCED FIRE AND SMOKE PROTECTION

These tried and tested products not only provide exceptional fire and smoke protection and peace of mind for occupants - they also enhance a building's airtightness and air quality while improving energy efficiency and moisture management.

DuPont™ AirGuard® FR System Tape

For use with DuPont™ AirGuard® A2 FR AVCL

PRODUCT DESCRIPTION & APPLICATION


DuPont™ AirGuard® FR System Tape is a fire retardant, single-sided tape, with A2 Fire Class to EN 13501. Specially formulated for use with DuPont™ AirGuard® A2 FR AVCL for sealing all horizontal and vertical laps and around penetrations.

COMPOSITION

Glass fibre carrier with lacquered reflective aluminium surface and specially formulated adhesive backing and paper release liner.

SPECIFICATIONS

- Fire retardant
- A2-s1,d0 fire class with DuPont™ AirGuard® A2 FR AVCL
- A2-s1,d0 fire class on gypsum plasterboard/CP board
- Surpasses current fire regulations for membranes used in external walls
- Suitable for all building types, heights and proximities
- 100% Airtight – for energy efficiency
- High vapour resistance – limits interstitial condensation
- Reflective (low emissivity 0.05)
- Exceptional tensile strength characteristics
- ~~Not hand tearable, please use cutting tool.~~



TECHNICAL DATA DuPont™ AirGuard® FR System Tape		
PROPERTY	VALUE	STANDARD
Stylename	1310FR	
Roll size	75mm x 25m	
Thickness	0.16mm	EN 1849-2
Weight	215g/m ²	EN 1849-2
Fire Class	A2	EN 13501-1
SD Value	>1500m	EN 1931
Emissivity	0.05	ASTM C1371
Tensile Strength	MD: 800 N/50mm XD: 800 N/50mm	EN 12311-1 with mod. to EN 13859
Nail Tear	MD: 170 N XD: 150 N	EN 12310-1 with mod. to EN 13859
Elongation	MD: 4% XD: 4%	EN12311-1 with mod. to EN 13859
Shear Resistance	300 N/50mm	EN 12317-2
Peel Resistance	7 N/25mm	EN 12316-2
Peel Force	8 N/25mm	EN1895
Temperature range	-40 to 80°C	
Watertightness	Pass	EN 1928

For further information please contact:

DuPont™ Tyvek® Building Knowledge Centre
Bristol & Bath Science Park
Dirac Crescent
Emersons Green
Bristol BS16 7FR

Technical: 0117 970 9454/9455
Sales: 0117 970 9456



www.FlameRetardant.tyvek.com

www.building.dupont.co.uk

www.energy-efficiency.dupont.com

Visit: www.building.dupont.co.uk


Technical enquiries: Tyvek.construction@dupont.com

DuPont®, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2021 DuPont.

DuPont™ Tyvek® and DuPont™ AirGuard®

DuPont™ Tyvek® is at the forefront of building science, meeting the building codes of today and the future with construction materials you can trust. For the ultimate energy efficiency solution and the inner strength that buildings need, DuPont™ Tyvek® partners AirGuard®, for superior performance and reliability in internal airtightness. With today's focus on the reduction of emissions and improved energy efficiency, you can count on a brand that has been at the heart of building solutions for decades and has a global building knowledge network. Tyvek® and AirGuard® are your guarantee of unbeatable energy efficiency.

With Tyvek® and AirGuard®, Trust is Built In.



For additional information please contact:

DuPont™ Tyvek® Building Knowledge Centre
Bristol & Bath Science Park
Dirac Crescent
Emersons Green
Bristol, UK
BS16 7FR

Technical: 0117 970 9454/9455

Sales: 0117 970 9456

Technical enquiries: tyvek.construction@dupont.com

www.building.dupont.co.uk

www.construction.tyvek.co.uk

www.energy-efficiency.dupont.com

For help with projects please contact our technical team at the Tyvek® Building Knowledge Centre or one of our Regional Managers (details above and on our web sites) For Installation guides and videos, technical data sheets, certification, case studies and other useful information

