

DUPONT™ TYVEK® GRAPHICS

Ordering guide: 2014

Tyvek® Graphics rolls

General conditions for ordering from DuPont Luxembourg:

- Minimum order quantity: please refer to price list and DuPont customer service. A number of versions may be mixed together.
- Roll width < 1 m: please check the number of rolls per pallet with customer service.
- Non-standard roll width: check availability with customer service.
- Minimum and maximum lengths may vary by from the nominal length +/- 5 % due to variations in the thickness of Tyvek®.
- Internal mandrel diameters available: 76 (3") or 152 mm (6"). Roll lengths remain the same.
- Lead times are indicated on the price list. Standard styles take 2 weeks plus transportation time and non-standard styles take 4 weeks plus transportation time. References with an asterisk (*) take 6 weeks plus transportation time. Please contact customer service.
- **The values enclosed herewith are provided for information only. Please contact our customer service for our latest sales terms and existing product codes.**

Classification	Versions	g/m²	Remarks	Mandrels (in mm)	Widths (in mm)	Lengths (in linear metres)		
						External roll diameter		
						550 mm	711 mm	990 mm
Tyvek® Classic standard	1025D	42.5		76 and 152	500-3,000		3,285	6,570
	1057D	55		76 and 152	500-3,000		2,500	5,000
	1058D	55	For self-adhesive coating only	76 and 152	500-2,900		2,500	5,000
	1073D	75		76 and 152	500-3,000		2,000	4,000
	1082D	105		76 and 152	500-2,900		1,500	3,050
Tyvek® Soft non-standard	1442R	43	OD 550 mm: 4 rolls per pallet OD 711 mm: 1 roll per pallet OD 990 mm: 1 roll per pallet	76	1,524	1,800	3,100	6,200
	1473R*	73	NB Lead time: 6 weeks OD 550 mm: 4 rolls per pallet OD 711 mm: 2 rolls per pallet	76	1,524	1,030	2,050	4,100

Classification	Versions	g/m ²	Remarks	Mandrels (in mm)	Widths (in mm)	Lengths (in linear metres)		
						External roll diameter		
						550 mm	711 mm	990 mm
Tyvek® approved for direct food contact and toy safety	1025B*	43	NB Lead time: 6 weeks No corona or antistatic treatment	76 and 152	500-2,900		3,360	6,720
	1051B*	65	NB Lead time: 6 weeks No corona or antistatic treatment	76 and 152	500-2,900		2,290	4,580
	1071B*	75	NB Lead time: 6 weeks No corona or antistatic treatment	76 and 152	500-2,900		1,990	3,980

Terms and conditions for ordering Tyvek® Brillion™ from DuPont Luxembourg (in addition to general terms and conditions):

- The lead time for widths between 500 mm and 2,200 mm is 4 weeks from order receipt plus transportation time.
- Calendered and smooth on both sides.

Classification	Versions	g/m ²	Remarks	Mandrels (in mm)	Widths (in mm)	Lengths (in linear metres)	
						External roll diameter	
						600 mm	840 mm
Tyvek® Brillion™ non-standard	4158D	55	Recommended for self-adhesive coating	76 and 152	500-2,200	2,420	4,860
	4173D	75		76 and 152	500-2,200	1,950	3,900

More information on the product's industrial health and safety are available on request. The information provided here was drawn up on the basis of the best facts available to us. This information is provided as a guideline and with the sole aim of helping you to carry out tests to determine whether our products are suited to your intended use. This information may be changed as new knowledge or information becomes available. Where the particular conditions for using its products are not checked, DuPont de Nemours accepts no obligation to achieve a specific result or any liability as regards the use of this information. Furthermore, this publication may not be considered a user licence nor is it aimed at suggesting methods of breaching any existing patent rights.

For information on direct orders, please contact customer service:
 DuPont de Nemours (Luxembourg) S.à r.l.
 L-2984 Luxembourg
 Tel.: +352-3666-5111
 Toll free: 00800 387 66 858
 Email: Tyvek.Europe@dupont.com



The miracles of science™