

DuPont™ Cyrel® EVO 2000 ECDLF

Exposure, Dryer & Light Finisher

The DuPont™ Cyrel® EVO 2000 ECDLF is a combined exposure unit with automatic lid and integrated dryer (4 drawers) and light finisher. It exposes, post-exposes and finishes high quality photopolymer plates up to a maximum format of 1,200 x 1,600 mm (47" x 63").

Features Exposure Light Finisher Section

- Maximum plate size 1,200 x 1,600 mm (47" x 63")
- Clamshell design with automatic pneumatic lid that contains integral safety switches
- Light integration system, which automatically compensates for any UV output variations
- New lamps air cooling system with temperature control
- Optical fibers lamp control
- Newly designed control display for optional installation on right or left side of the unit
- Lamp pre-heating function
- Userfriendly back exposure test function

Features Dryer

- 4 sealed drawers to prevent any leak of fumes
- Drying temperature reached in a very reduced time thanks to the new hot air generation and circulation system.
- Automatic pre-heat system and automatic switch off option
- Optimal T° uniformity thanks to 2 separate T° controls interfaces
- New air suction system design to ensure a faster plate drying



Product Features

The exposure section is a clamshell design holding 42 UV-A fluorescent tubes with built-in reflectors.

The unit is fitted with a light integrator that compensates for the decrease in light output as the tubes age.

To meet the demanding needs of high quality plates, the user can easily customize the 24 different set-ups for back exposure, main exposure.

Each fluorescent tube is constantly monitored by a light guide, giving the operator a visual on/off indication. There are three-time counters embedded in the touch screen control panel to keep track of the number of hours the UV-A and UV-C tubes have been in operation.

The post exposure and light finisher section hold 23 UV-C and 24 UV-A tubes. The control panel allows the user to perform post exposure and finishing in a preferred sequence, or simultaneously. The post-exposure (UVA) and light-finisher section has 24 different set-ups that can be easily customized.

DuPont™ Cyrel® EVO 2000 ECDLF

Exposure, Dryer & Light Finisher

Technical Data

General	Details	Other Notes
Equipment Name	DuPont™ Cyrel® EVO 2000 ECDLF	Exposure, Dryer & Light Finisher
SAP Article Number	D15551711	
Max. Nominal Plate Width	1200 mm	47 inch
Max. Nominal Plate Length	1600 mm	63 inch
Plate Thickness	up to 7.0 mm	up to 0.276 inch
UV-A Tubes Wave Length	360 nm – 380 nm	42 tubes (exposure) GMC M300506001 CY CNS LAMP, UVA, 80 W, 1.5 M 24 tubes (LF) GMC M300506001 CY CNS LAMP, UVA, 80 W, 1.5 M
UV-C Tubes Wave Length	254 nm	23 tubes, GMC D12374309 CY CNS LAMP, UVC, 60-95W, 1.5 M
Electrical (Field Configurable)	400 Volt – 50/60 Hz 230 Volt – 50/60 Hz	3PH/N/PE 11kW 17A 3PH/PE 11kW 29A
Power (Nominal)	9.5 kW	
Current (Nominal Load)	15 Amp @ 400 Volt; 25 Amp @ 230 Volt	
Connecting Wires	400 Volt configuration; 230 Volt configuration	5G6
Grounding	≤ 0.1 Ω	Ground bar to equipment frame and to electrical supply ground
Exhaust	1 x 160 mm	1000 m3 / h
Environmental Data	Temperature range: 17°C to 28°C (63°F to 82°F)	Relative humidity from 10% to 80% non-condensing
Compressed Air Supply	Min. 7 bar	
Dimensions	Uncrated	Crated
D	2,640 mm (103.9")	2,930 mm (115.3")
W	1,740 mm (68.5")	1,930 mm (76.0")
H	1,046 mm (41.2")	1,590 mm (62.6")
H (open)	2,660 mm (104.7")	
Weight	1,250 kg (2,756 lbs)	Crated: 1,530 kg (3,373 lbs)
Color	DuPont Red and Grey	

The DuPont Advanced Printing portfolio of products includes the DuPont™ Cyrel® brand of photopolymer plates (analog and digital), Cyrel® platemaking equipment, Cyrel® round sleeves and the revolutionary Cyrel® FAST thermal system.



cyrel.eu

For more information on DuPont™ Cyrel® or other DuPont products, please visit our website.

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. It may be subject to revision as new knowledge and experience becomes available. This information is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. Since we cannot anticipate all variations in end-use and disposal conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right. EDS-EU0060-EN (05/2020)

DuPont™, the DuPont Oval Logo, and all products, unless otherwise noted, denoted with ™, ® or ® are trademarks, service marks or registered trademarks of affiliates of DuPont de Nemours, Inc. Copyright © 2020 DuPont de Nemours Inc. All rights reserved.