

DuPont™ Cyrel® Punch

Punch

The Cyrel® Punch provides fast and efficient punching of exposed Cyrel® photopolymer plates up to a nominal width of 1.330 mm (52 inch) and up to a nominal thickness of 7.25mm (0.285 inch).



Application

- Flexible packaging
- Carrier bags
- Folding cartons
- Pre-print liner
- Beverage cartons
- Envelopes
- Film Printing
- Rough Paper substrate
- Corrugated pre print
- Corrugated post print
- Paper
- Sacks
- Board

Product Features

- Maximum plate width 1,330 mm
- Fast and effective plate punching
- High repeatable accuracy
- Simple to operate
- Optimum productivity

The Cyrel® Punch is designed and constructed to warrant exact and systematic punching of unprocessed Cyrel® photopolymer plates.

The Cyrel® Punch operates using compressed air and is designed and constructed for safe operations. Holes punched by the Cyrel® Punch correspond to the transport bar delivered with the Cyrel® Solvent Processors and have standard spacing of 80-90-80 mm. On the entire length are distributed 15 punches with a diameter of 6mm (0.236 inch).

When spacing of 90-90-90 mm is required, the punch cylinders can be adjusted to this position via the holes provided.

The punch is equipped with a universal compressed air connector for connecting to an existing compressed air line or to a separate compressor unit.

The Cyrel® Punch unit is delivered in one piece, after transportation to its final location, no adjustment is necessary.

DuPont™ Cyrel® Punch

Punch

Technical Data

General	Details	Other Notes
Equipment Name	DuPont™ Cyrel® Punch	Automatic
SAP Article Number	M163953	
Packing	Crated	
Max. nominal plate width	1,330 mm – 52 inch	
Number of punches	15	
Hole diameter	6 mm – 0.236 inch	
Max plate thickness	7.25 mm – 0.285 inch	
Electrical (field configurable)	NA	
Power (nominal)	NA	
Current (nominal load)	NA	
Grounding	NA	
Exhaust	NA	
Environmental Data	Temperature range 17°C to 28°C – 63°F to 82°F	Relative humidity From 20% to 85% non-condensing
Compressed Air supply	6 bar	87 psi
Dimensions	Uncrated	Crated
L	1,530 mm (60.3")	1,390 mm (54.8")
W	730 mm (28.8")	600 mm (23.7")
H	410 mm (16.5")	230 mm (9.0")
Weight	94 kg (207.2 lbs)	44 kg (97.0 lb)
Colour	DuPont Grey	

DuPont Industrial Solutions brings together leading technologies and products for the printing and package printing industries. DuPont™ Cyrel® is one of the world's leading flexographic platemaking systems in digital and conventional formats, including DuPont™ Cyrel® brand photopolymer plates (analogue and digital), Cyrel® platemaking equipment, Cyrel® round sleeves, Cyrel® plate mounting systems and the revolutionary Cyrel® FAST thermal system.



cyrel.eu

For more information on DuPont™ Cyrel® or other DuPont products, please visit our website.

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. It may be subject to revision as new knowledge and experience becomes available. This information is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. Since we cannot anticipate all variations in end-use and disposal conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.

DuPont™, the DuPont Oval Logo, and Cyrel® are trademarks or registered trademarks of DuPont or its affiliates. Copyright © 2021 DuPont de Nemours Inc. All rights reserved.

PDS-EU0052-EN (4/21)