## < DUPONT >

# DuPont<sup>™</sup> Cyrel<sup>®</sup> EASY ESER

Built in flat top dot digital plate with an engineered surface

### **Applications**

- Flexible packaging
- Tag and Label



Cyrel<sup>®</sup> ESER is the latest addition to the DuPont<sup>™</sup> Cyrel<sup>®</sup> EASY platform with built-in flat top dot technology and is formulated for solvent processing. In addition to excellent print quality in terms of highlights, smoothness of vignettes and solid ink densities, DuPont<sup>™</sup> Cyrel<sup>®</sup> ESER comes with greater platemaking latitude. With exceptional robustness, the plate delivers excellent longevity and cleanliness on press. Cyrel<sup>®</sup> EASY ESER has an engineered surface for high solid ink density without micro-screening.

#### **Product Features and Benefits**

- A plate that is based on advancements to Cyrel<sup>®</sup> EASY polymer that delivers high ink transfer and resolution.
- The advanced polymer formulation provides exceptional robustness while enabling the plates to run cleaner for longer on press.
- Ideally suited for extended gamut printing.
- The flat top dot shape compresses less, providing a more consistent and stable print surface.
- Higher latitude and better uniformity reduce setup time on press.
- The smaller shape flat top dot allows higher resolution and a very wide tonal range for crisper sharper printing results.
- The EASY ESER's standardised, engineered surface allows higher solid ink density and lower graininess.
- No micro-screening needed, allowing for higher Cyrel® Digital Imager (CDI) productivity.
- The simplified workflow reduces errors in the exposure/ laminate step.
- Recommended for printing on smooth surfaces and film substrates.

#### Printing Ink and Solvent Compatibility

Cyrel<sup>®</sup> EASY ESER plates offer excellent compatibility with solvent-based, water-based, and UV inks.

#### **Process of Use**

Expose the plate through the back to establish the floor and maximise sensitivity. Back exposure varies according to relief required. Remove the protective coversheet, and image the plate with the CDI. Expose the front of the plate surface. Process the plate in the Cyrel<sup>®</sup> solvent processor to remove unexposed polymer. Finish the plate in a light finisher to eliminate surface tackiness.

#### Mounting

DuPont<sup>™</sup> Cyrel<sup>®</sup> Microflex mounting devices are recommended for mounting Cyrel<sup>®</sup> EASY ESER plates. The double-sided adhesive should first be applied to the cylinder or sleeve—not the plate—to ensure easier and precise laydown. The polyester base will maintain accurate register even with large plates.

### DuPont<sup>™</sup> Cyrel<sup>®</sup> EASY ESER

Built in flat top dot digital plate with an engineered surface

#### Storage – Raw Material

Store unexposed plates in a cool area (4–32°C, 40–90°F), away from direct sources of heat. Humidity control is not required. Cyrel® EASY ESER is foam interleaved to provide maximum protection of the plate after manufacture and during transportation and storage. Plates should be stacked flat. Plates should not be exposed to direct sunlight or excessive white light. Continuous exposure to very high ozone concentrations should be avoided.

#### Handling – Raw Material

Like all photopolymer plates, Cyrel<sup>®</sup> EASY ESER plates should be handled under UV free light; e.g., fluorescent tubes covered with amber sleeves.

#### Storage – Finished Plates

After printing, plates should be thoroughly cleaned with compatible solvent before storing. They may be stored on cylinders, sleeves or demounted and stored flat.

Plates Available	Thickness	Durometer	Image Reproduction	Min. Positive Line Width	Min. Isolated Dot Size	Relief Depth
Cyrel EASY Solvent ESER 45	0.045" (1.14 mm)	76-78 Sh A	1-98% @ 190 lpi (75 L/cm)	0.10 mm (4 mil)	0.10 mm	0.60 mm
Cyrel EASY Solvent ESER 67	0.067" (1.70 mm)	68-70 Sh A	1-98% @ 190 lpi (75 L/cm)	0.10 mm (4 mil)	0.10 mm	0.70 mm

DuPont Advanced Printing brings together leading technologies and products for the printing and package printing industries. DuPont<sup>™</sup> Cyrel<sup>®</sup> is one of the world's leading flexographic platemaking systems in digital and conventional formats, including DuPont<sup>™</sup> Cyrel<sup>®</sup> brand photopolymer plates (analog and digital), Cyrel<sup>®</sup> platemaking equipment, Cyrel<sup>®</sup> round sleeves, Cyrel<sup>®</sup> plate mounting systems and the revolutionary Cyrel<sup>®</sup> FAST thermal system.

## For more information on DuPont<sup>™</sup> Cyrel<sup>®</sup> or other DuPont products, please visit our website.

The information provided in this data sheet corresponds to our knowledge on the subject at the date of its publication. It may be subject to revision as new knowledge and experience becomes available. This information is not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. Since we cannot anticipate all variations in end-use and disposal conditions, DuPont makes no warranties and assumes no liability in connection with any use of this information. It is intended for use by persons having technical skill, at their own discretion and risk. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right. DuPont<sup>\*\*</sup>, the DuPont Oval Logo, and Cyrel<sup>®</sup> are trademarks or registered trademarks of DuPont or its affiliates. Copyright © 2019 DuPont de Nemours Inc. All rights reserved. PDS-EU0091-EN (10/20)

