



TSCHF5SWHDE

# Tyvek® 200 EasySafe

DuPont™ Tyvek® 200 EasySafe CHF5. Optimized protection against fine particles and low-level sprays yet breathable and lightweight in a white hooded coverall. Features stitched external seams, a respirator fit two-piece hood, elasticated wrists, ankles, face, and waist (stitched-in), a pin lock slider zipper pull and a storm flap. Suitable for remediation, industrial cleaning, and general manufacturing applications.

Name	Description
Full Part Number	TSCHF5SWHDE
Fabric/Materials	Flash spun HDPE
Design	Hooded coverall with elastics
Seam	Stitched (external), yellow
Color	White
Sizes	SM, MD, LG, XL, 2X, 3X
Quantity/Box	100 per box, individually packed.

## FEATURES & PRODUCT DETAILS

DuPont™ Tyvek® 200 EasySafe. Hooded coverall available in white, sizes SM to 3X. Robust yet lightweight (<180g per garment). 2-piece hood. Elasticated face, wrists, waist and ankles.

Tyvek® 200 fabric is a new and unique optimised polyethylene nonwoven from DuPont. It is softer and with a more open structure than Tyvek® 500/600. It is therefore less protective than Tyvek® 500/Tyvek® 600, but offers adequate Type 5 and 6 barrier protection and remains both air and moisture vapour permeable. Tyvek® 200 Easysafe applications include remediation and industrial cleaning and general manufacturing.

- Certified according to Regulation (EU) 2016/425.
- Chemical protective clothing, Category III, Type 5 and 6.
- EN 1073-2 (protection against radioactive contamination)
- Antistatic treatment (EN 1149-5) – on inside and outside
- Stitched external seams in yellow for visual identification and differentiation
- Soft touch fabric for wearer comfort
- Optimised design and packaging

## **ADDITIONAL EQUIPMENT NEEDED**

- Please read, understand and follow the Instructions For Use
- Wear other appropriate PPE such as, but not limited to, respiratory, eye, head, hand, and foot protection based on the hazard assessment.

## SIZES

Product Size	Article Number	Additional info
SM	D14886039	
MD	D14886047	
LG	D14886050	
XL	D14886064	
2X	D14886075	
3X	D14886081	

## Physical Properties



Data relating to mechanical performance of the fabrics used in DuPont chemical protective clothing, listed for the selected garment according to the test methods and relevant European standard, if applicable. Such properties, including abrasion and flex-cracking resistance, tensile strength and puncture resistance can help in the assessment of protective performance.

Property	Test Method	Typical Result	EN
Abrasion Resistance <sup>7</sup>	EN 530 Method 2	>10 cycles	1/6 <sup>1</sup>
Colour	N/A.	White	N/A
Flex Cracking Resistance <sup>7</sup>	EN ISO 7854 Method B	>40000 cycles	5/6 <sup>1</sup>
Puncture Resistance	EN 863	>5 N	1/6 <sup>1</sup>
Resistance to water penetration	AATCC 127	>9 kPa	N/A
Surface Resistance at RH 25%, outside <sup>7</sup>	EN 1149-1	< 2,5 • 10 <sup>9</sup> Ohm	N/A
Surface Resistance at RH 25%, inside <sup>7</sup>	EN 1149-1	< 2,5 • 10 <sup>9</sup> Ohm	N/A
Tensile Strength (MD)	DIN EN ISO 13934-1	>30 N	1/6 <sup>1</sup>
Tensile Strength (XD)	DIN EN ISO 13934-1	>30 N	1/6 <sup>1</sup>
Trapezoidal Tear Resistance (MD)	EN ISO 9073-4	>10 N	1/6 <sup>1</sup>
Trapezoidal Tear Resistance (XD)	EN ISO 9073-4	>10 N	1/6 <sup>1</sup>

1 According to EN 14325 2 According to EN 14126 3 According to EN 1073-2 4 According to EN ISO 14116 12  
 According to EN ISO 11612 5 Front Tyvek ® / Back 6 Based on test according to ASTM D-572 7 See Instructions  
 for Use for further information, limitations and warnings > Larger than < Smaller than <= Smaller than or equal to N  
 /A Not Applicable STD DEV Standard Deviation

## COMFORT



The comfort of a protective garment during use is largely determined by its weight, its permeability to vapour and air (breathability) and insulating properties. Data on these attributes is provided according to test method and, as with other data, can be compared by garment.

Property	Test Method	Typical Result	EN
Air Permeability (Gurley method)	TAPPI T460	26 s	N/A

2 According to EN 14126    5 Front Tyvek® / Back    > Larger than    < Smaller than    <= Smaller than or equal to    N/A  
Not Applicable

## PENETRATION AND REPELLENCY



A specific test method, EN ISO 6530, is used to measure the indexes of penetration, absorption and repellency of protective clothing material exposed to liquid chemicals. Results listed here reflect the penetration resistance and repellency of DuPont fabrics to 30% sulphuric acid and 10% sodium hydroxide.

Property	Test Method	Typical Result	EN
Repellency to Liquids, Sodium Hydroxide (10%)	EN ISO 6530	>95 %	3/3 <sup>1</sup>
Repellency to Liquids, Sulphuric Acid (30%)	EN ISO 6530	>90 %	2/3 <sup>1</sup>
Resistance to Penetration by Liquids, Sodium Hydroxide (10%)	EN ISO 6530	<5 %	2/3 <sup>1</sup>
Resistance to Penetration by Liquids, Sulphuric Acid (30%)	EN ISO 6530	<5 %	2/3 <sup>1</sup>

<sup>1</sup> According to EN 14325 > Larger than < Smaller than <= Smaller than or equal to

## GARMENT PERFORMANCE



Information relating to the protective performance of a garment according to European standards where applicable. Includes important characteristics such as protection against radioactive contamination, seam strength and shelf life. Inward leakage and resistance to penetration by liquids, according to the relevant Type classification, are also detailed.

Property	Test Method	Typical Result	EN
Type 5: Inward Leakage of Airborne Solid Particulates	EN ISO 13982-2	Pass	N/A
Type 5: Inward Leakage <sup>11</sup>	EN ISO 13982-2	2.0 %	N/A
Type 6: Resistance to Penetration by Liquids (Low Level Spray Test)	EN ISO 17491-4, Method A	Pass	N/A
Nominal protection factor <sup>7</sup>	EN 1073-2	>5	1/3 <sup>3</sup>
Seam Strength	EN ISO 13935-2	>50 N	2/6 <sup>1</sup>

1 According to EN 14325 3 According to EN 1073-2 12 According to EN ISO 11612 13 According to EN 11611 5  
 Front Tyvek ® / Back 6 Based on test according to ASTM D-572 7 See Instructions for Use for further information,  
 limitations and warnings 11 Based on the average of 10 suits, 3 activities, 3 probes > Larger than < Smaller than <=  
 Smaller than or equal to N/A Not Applicable \* Based on lowest single value

## WARNING

- The garment does not protect against ionizing radiation.
- This garment and/or fabric are not flame resistant and should not be used around heat, open flame, sparks or in potentially flammable environments.
- The information provided herein corresponds to our knowledge on the subject at the date of its publication. This information may be subject to revision as new knowledge and experience becomes available. The data provided fall within the normal range of product properties and relate only to the specific material designated; these data may not be valid for such material used in combination with any other materials or additives or in any process, unless expressly indicated otherwise. The data provided should not be used to establish specification limits or used alone as the basis of design; they are not intended to substitute for any testing you may need to conduct to determine for yourself the suitability of a specific material for your particular purposes. Since DuPont cannot anticipate all variations in actual end-use conditions DuPont makes no warranties and assumes no liability in connection with any use of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent rights..